DUCHESNE COUNTY MONUMENT SURVEY RECORD


LINE	BEARING	DISTANCE
L 1	N 43°55'01" E	30.83'
L2	N 40°16'50" W	18.32'
	S 26°50'57" W	13.44
	S 40°19'34" E	23.66'

FOUND DUCHESNE COUNTY MONUMENT ON COPPER WELD AT 1/4 CORNER

CAP

1/4 CORNER

1/2" REBAR WITH GREEN CAP



 \leq


1/2" REBAR WITH GREEN CAP •

1/2" REBAR WITH GREEN CAP

1/4 SEC 6 -SEC 5

T4S R8W

U.S.B.&M.







NOTE:
THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED
FROM G.P.S. OBSERVATIONS AT A CONTROL POINT
LOCATED AT LAT. 40°11'44.89846"N AND LONG.
110°49'41.53893"W USING THE UTAH STATE G.P.S.
VIRTUAL REFERENCE STATION CONTROL NETWORK
MAINTAINED AND OPERATED BY THE AUTOMATED
GEOGRAPHIC REFERENCE CENTER

DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND ORIGINAL MARKED STONE WITH 1/2" REBAR WITH YELLOW CAP, ÁLONGSIDE AT POSITION OF 1/4 CORNER



REPLACED STONE WITH A DUCHESNE COUNTY ALUMINUM 2½" DIA. CAP ON 30" FLARED PIPE MONUMENT AT POSITION OF CORNER



PHOTO OF MARKINGS ON MONUMENT

STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET) NAD83 UTAH CENTRAL ZONE N: 7228375.105 F: 1830201.312 NAVD88 EL: 7770.48'

40°09'42.42149" N LATITUDE: 110°49'15.32106" W LONGITUDE:

ELLIPSOID HEIGHT: 7715.15'

(GEOID 03 CONUS)

PUBLIC LAND SURVEY SYSTEM GCDB ID NO.

UT300040S0080W0_200640



PHOTO OF MONUMENT FACING NORTH

CERTIFICATION

<u>Jerry D. Allred</u> , Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date <u>IO MAY'19</u>

Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor

